

1.4 Konstruktionsvollholz Fichte

Nichtsichtqualität

Holzfeuchte 15 +/- 3 %

maßhaltig egalisiert für den nichtsichtbaren Bereich

Ab 7,50 Meter Länge keilgezinkt



Stärke in mm	Breite in mm	Länge						
		5,00 m	7,50 m	8,00 m	8,50 m	9,00 m	10,00 m	13,00 m
40	60	•						
40	80	•						
60	60	•						
60	80	•						
60	100	•						•
60	120	•						•
60	140	•						•
60	160	•						•
60	180							•
60	200							•
60	220							•
60	240							•
80	80	•						
80	100	•						•
80	120	•	•				•	•
80	140	•	•	•	•	•	•	•
80	160	•	•	•	•	•	•	•
80	180	•	•	•	•	•	•	•
80	200	•	•	•	•	•	•	•
80	220							•
80	240							•
100	100	•						•
100	120	•	•					•
100	140		•		•		•	•
100	160		•		•		•	•
100	180		•		•		•	•
100	200	•	•	•	•		•	•
100	220							•
100	240							•
120	120	•						•
120	140							•
120	160							•
120	180							•
120	200							•
120	220							•
120	240							•
140	140	•						•
140	160							•
140	180							•
140	200							•
140	240							•
160	160							•